

## Double Sided Foam Tape – DF F6X64

Product Description	<ul style="list-style-type: none"><li>• Double sided PE foam tape</li><li>• Coated on both sides with high performance acrylic adhesive</li><li>• Provides good initial tack and high adhesion to a variety of surfaces</li></ul>		
Technical Performance	Adhesive Type	Solvent-based acrylic adhesive	
	Carrier	Closed cell cross-linked PE foam	
	Tape	1.5mm ± 0.02mm (1/16” ± 0.8 mil)	Test method: PSTC-33
	Liner	0.070mm ± 0.010mm (3.0mil ± 0.4mil)	Test method: PSTC-33
	Adhesion to steel	2.0 kg/25mm (70 oz./in)	Test method: PSTC-01
	80°C Cohesion	1440 minute ↑	Test method: PSTC-7
	Elongation at break	100%	Test method: PSTC-131
	Service Temperature	-20 °C ~ 100 °C (-4 °F ~ 212 °F)	
Color	Tape Color	White	
	Release Liner Color	White Paper	
Storage Details	Shelf life recommended 6 months from the date of dispatch at the moderate temperature and humidity environment		

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.