

## Double Sided Tape – DL F64C

<b>Product Description</b>	<ul style="list-style-type: none"> <li>• 0.48 mil PET film backing</li> <li>• High performance capable, double coated, PET film tape</li> <li>• Two sided coating of acrylic-based, pressure sensitive adhesives</li> </ul>		
<b>Application</b>	<ul style="list-style-type: none"> <li>• Mounting if metal or plastic badges and signs</li> <li>• Excellent handling performance in converting processes</li> </ul>		
<b>Features/Benefits</b>	<ul style="list-style-type: none"> <li>• Excellent performance to cold weathering</li> </ul>		
<b>Technical Performance</b>	Tape thickness	0.09 mm (3.54 mil)	Test method: PSTC-133
	Adhesion to steel	0.52 kg/cm (45.8 oz./in)	Test method: ASTM D-1000
	23 °C Cohesion to steel	>240 minute	Test method: PSTC-7
	Elongation at break	75%	Test method: PSTC-131
	Tensile strength	2.1 kg/cm (12.13 lb./in)	Test method: PSTC-131
<b>Storage Details</b>	Recommended one year shelf life from date of dispatch if kept at moderate temperatures and humidity levels		

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.