

Transfer Tape – DRAT20B

Product Description	<ul style="list-style-type: none"> • Adhesive: Acrylic (solvent based) • Carrier: None • Liner: Glassine, mustard color 	
Application	<ul style="list-style-type: none"> • Industrial foams, gaskets and other lamination • Core starting • Splicing of papers, film and others 	
Features/Benefits	<ul style="list-style-type: none"> • Economical • Good initial tack • Transparent adhesive, aging resistance, and acid free (PH 7, neutral) • Glass fiber reinforced, for cleaner cut and easier handling 	
Technical Performance	Note: The following technical information and data should be considered representative or typical only.	
	Total Thickness	0.120 mm (4.7 mil)
	Adhesive Thickness	0.050 mm (2.0 mil)
	Adhesion to steel	0.33 kg/cm (30 oz./in)
	Shear Strength / Steel	➤ 93 Hour / kg
	Temperature Range	80° C / 176° F (long) 200° C / 392° F (short)
Storage Details	Shelf life recommended one year from the date of dispatch at the moderate temperature and humidity environment.	

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.