

## Double Sided Tape – DT 63G

<b>Product Description</b>	<ul style="list-style-type: none"> <li>• General purpose, double coated tissue paper tape</li> <li>• Two sided coating of acrylic-based, pressure sensitive adhesives.</li> </ul>		
<b>Application</b>	<ul style="list-style-type: none"> <li>• Ideal for bonding metals, nameplates, cloth and plastic surfaces</li> </ul>		
<b>Features/Benefits</b>	<ul style="list-style-type: none"> <li>• High quality acrylic adhesive allows for use on wide variety of surfaces.</li> <li>• Heavy-duty release paper allows for easy manual handling.</li> <li>• No known hazards.</li> </ul>		
<b>Technical Performance</b>	Tape thickness	0.085 mm (3.35 mil)	Test method: PSTC-133
	Adhesion to steel	0.39 kg/cm (35.24 oz./in)	Test method: ASTM D-1000
	23 °C Cohesion to steel	1440 min.	Test method: PSTC-107
	Elongation at break	2% max.	Test method: PSTC-131
	Tensile strength	0.8 kg/cm (4.4 lb./in)	Test method: PSTC-131
<b>Storage Details</b>	Recommended one year shelf life from the date of dispatch at the moderate temperature and humidity levels		

### Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. **ACHEM MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at ACHEM's option, to replace or repair the ACHEM product or refund the purchase price of the ACHEM product. Except where prohibited by law, ACHEM will not be liable for any loss or damage arising from this ACHEM product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.