

Double Sided Tape – DT 63H

Product Description	<ul style="list-style-type: none"> • High temperature resistance, high performance, double coated tissue paper tape. • Two sided coating of acrylic-based, pressure sensitive adhesives. 		
Application	<ul style="list-style-type: none"> • Strong adhesion allows attachment to many materials including metals and the majority of plastics. • Thick acrylic adhesives permit bonding to many irregular or textured surfaces such as heavy papers or corrugated boards. 		
Features/Benefits	<ul style="list-style-type: none"> • High quality and strong holding power acrylic adhesive allows for use on wide variety of surfaces. • Excellent resistance to heat, weathering and thermal creep. • Heavy-duty release paper allows for easy manual handling. • No known hazards. • Application Temperature is: -20 °C ~ 80 °C / -4 °F ~ 176 °F). 		
Technical Performance	Tape thickness	0.130 mm (5.12 mil)	Test method: PSTC-133
	Adhesion to steel	0.39 kg/cm (35.24 oz./in)	Test method: ASTM D-1000
	23 °C Cohesion to steel	1440 minute	Test method: PSTC-7
	Elongation at break	2.0%	Test method: PSTC-131
	Tensile strength	0.8 kg/cm (4.4 lb./in)	Test method: PSTC-131
Storage Details	Recommended one year shelf life from the date of dispatch at the moderate temperature and humidity environment		

Note to Buyer: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the product for the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, expressed, implied, statutory or otherwise. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.