

## Double Sided Tape – F4D13

<b>Product Description</b>	<ul style="list-style-type: none"> <li>• Clarity, double sided polyethylene terephthalate (PET) film tape</li> <li>• Two sided coating of solvent acrylic, pressure sensitive adhesives</li> <li>• Excellent initial tack, holding power and weatherability</li> </ul>		
<b>Application</b>	<ul style="list-style-type: none"> <li>• Great for extruded profiles, tacking furniture molding and window decorations</li> </ul>		
<b>Features/Benefits</b>	<ul style="list-style-type: none"> <li>• Red MOPP double silicon liner</li> <li>• No known hazards</li> </ul>		
<b>Technical Performance</b>	Tape thickness	0.22 mm (8.7 mil)	Test method: PSTC-133
	Adhesion to steel	1.16 kg/cm (104 oz./in)	Test method: PSTC-1
	60 °C Cohesion to steel	>24 hour	Test method: PSTC-7
	Elongation at break	70~130%	Test method: ASTM D-882
	Tensile strength	4.0 kg/cm (22.4 lb./in)	Test method: ASTM D-882
<b>Storage Details</b>	Recommended one year shelf life from the date of dispatch at the moderate temperature and humidity environment		

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.