

## DC07G DUCT CLOTH TAPE

<b>Product Description</b>	• Polycloth Adhesive Tape	
<b>Construction</b>	Carrier	Woven polyester and cotton-coated, blended with LDPE
	Adhesive	Coated with vacuum hot melt adhesive (synthetic rubber)
	Color	Silver
<b>Physical Properties</b>	Note: The following technical information and data should be considered representative or typical only.	
	Total Thickness	0.17 ± 0.01 mm (0.7 ml)
	Adhesion to steel	≥ 47.5 oz/in
	Cohesion	N/A
	Tensile Strength	≥ 25N/cm
	Elongation at Break	10% - 20%
	Tack	N/A
	Unwind	N/A
	Standard Width	12 mm, 18mm, 24mm, 36mm, 48mm, 72mm, Custom Width
<b>Available Sizes</b>	Core Size	72 mm (3 in)
	Length	50M, 100M, Custom Length
	Storage	Clean and dry in a well ventilated area, preferably at a temperature between 50°~86° F (10°~ 30° C). Stored under these conditions, shelf life will be a minimum of 6 months.
<b>Temperature Conditions</b>	Application	5°~158° F (-15°~70° C)

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.