

PVC Electrical Insulating Tape - ET211 (BKC)

Product Description	<ul style="list-style-type: none">• Matte SPVC film coated with special rubber-based adhesive• Outstanding adhesion and conformability• UL listed		
Application	<ul style="list-style-type: none">• Used for electrically insulating joints and splices in wires and cables		
Features/Benefits	<ul style="list-style-type: none">• Suitable for uses under 600V or 80 °C (176 °F)• Ideal for all applications where UL listed, insulating materials are required• Non-corrosive, pressure-sensitive adhesive eliminates the need of heat, moisture, or other catalysts to affect application• Low lead		
Technical Performance	Tape thickness	7.0 mils (0.180 mm)	Test method: PSTC-33
	Adhesion to steel	16 oz./in (1.8 N/10 mm)	Test method: ASTM D1000
	Dielectric Strength	6.8 KV	Test method: ASTM D1000
	Elongation at break	180%	Test method: PSTC-31
	Tensile strength	14 lbs./in (25.5N/10 mm)	Test method: PSTC-31
Storage Details	Recommended one year shelf life from the date of dispatch at the moderate temperature and humidity environment.		

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.