

PVC Electrical Tape – ET24D

Product Description	<ul style="list-style-type: none"> General purpose electrical tape 	
Features/Benefits	<ul style="list-style-type: none"> PET film with solvent based acrylic adhesive Good adhesives, solvent resistance, heat-resistance and high strength Ideal for insulation and wrapping of all sorts of electrical coils UL recognized 	
Technical Performance	Total Thickness	0.060 mm (2.36 mil)
	Backing Thickness	0.025 mm (0.98 mil)
	Adhesion to Steel	0.6 kg/ 25 mm (21.2 oz./in)
	Tensile Strength	9.7 kg/ 25 mm (21.4 lb./in)
	Elongation	80%
	Breakdown Voltage	4.2 KV
	Temperature Resistance	130° C / 226° F
Storage Details	Shelf life recommended one year from the date of dispatch at the moderate temperature and humidity environment.	

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.