

## PVC Electrical Insulating Tape – ETK11

<b>Product Description</b>	<ul style="list-style-type: none"> <li>• Soft PVC film coated tape, suitably plasticized and stabilized</li> <li>• One sided coating of rubber-based, pressure sensitive adhesives</li> <li>• UL listed</li> <li>• Matte finish, low lead electrical tape</li> </ul>	
<b>Application</b>	<ul style="list-style-type: none"> <li>• Used for joining and splicing wires and cables for electrical insulation</li> </ul>	
<b>Features/Benefits</b>	<ul style="list-style-type: none"> <li>• Suitable for uses under 600V or 80 °C (176 °F)</li> <li>• Ideal for all applications where UL listed, insulating materials is required</li> <li>• Non-corrosive pressure-sensitive adhesive eliminates the need of heat, moisture, or other catalysts to effect application</li> <li>• No known hazards</li> </ul>	
<b>Technical Performance</b>	Note: The following technical information and data should be considered representative or typical only.	
	Total Thickness	0.18 mm (7.0 mil)
	Adhesion to steel	0.18 kg (16 oz./in)
	Tensile Strength	2.6 kg (14 lbs./in)
	Elongation at Break	200%
<b>Storage Details</b>	Shelf life recommended one year from the date of dispatch at the moderate temperature and humidity environment.	

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.