

House Sheathing Tape – HWX39

Product Description	<ul style="list-style-type: none"> • Biaxially Oriented Polypropylene (BOPP) film tape • High performance solvent based acrylic adhesive • Wide temperature range 		
Application	<ul style="list-style-type: none"> • Designed for sealing and joining seams, fixing cuts of house wrap sheathing material 		
Features/Benefits	<ul style="list-style-type: none"> • Good for sub-freezing temperature • Good tack and strong substrate on slightly irregular surfaces • Color: Red and White • No known hazards 		
Technical Performance	Tape thickness	0.07 mm (2.8 mil)	Test method: PSTC-133
	Adhesion to steel	0.40 kg/cm (35 oz./in)	Test method: ASTM D-1000
	50 °C Cohesion to steel	1,440 minute	Test method: PSTC-107
	Elongation at break	100~180%	Test method: PSTC-131
	Tensile strength	4.7 kg/cm (26.4 lb./in)	Test method: PSTC-131
Storage Details	Recommended one year shelf life from the date of dispatch at the moderate temperature and humidity environment		

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.