

PVC Industry Tape – STV10

Product Description	 Soft PVC film coated tape, suitably elasticized and stabilized Coated with rubber-based pressure sensitive adhesives on one side Shiny and premium colored strip tape, stand tape: white/red, white/green and yellow/black 	
Application	• It is used for industrial identification, color coding and pipe wrapping purpose	
Features/Benefits	 Suitable use at no more than 60 °C (140 °F) Has excellent anti-abrasion, flexible and resistant to acid, alkalis and oil With a non-corrosive pressure-sensitive adhesive, requiring no heat, moisture, or other manner of preparation to effect application No know hazards 	
Technical Performance	Note: The following technical information and data should be considered representative or typical only.	
	Total Thickness	0.16 mm (6.4 mil)
	Adhesion to steel	0.20 kg (17 oz./in)
	Tensile Strength	3.1 kg (17.6 lbs./in)
	Elongation at Break	180%
Storage Details	Shelf life recommended one year from the date of dispatch at the moderate temperature and humidity environment	

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.