

***Clear Advantage™* Selfwound Overlamination Film**

Product Description	#109T Clear Polypropylene Thermal Transfer Printable				
Construction	Film	Adhesive	Overall Thickness	Film Thickness	Adhesive Thickness
	Biaxially Oriented Polypropylene	Emulsion Acrylic	1.1 mil	0.8 mil ±3%	0.3 mil ± 3%
Physical Properties	Note: The following technical information and data should be considered representative or typical only.				
	Tensile Strength		14.5 lbs/in		
	Elongation at Break		153 %		
	Peel Adhesion		14.5 oz/in		
Operating Temperature	0 °F to 300 °F (nominal range)				
Special Features	• Thermal Transfer Printable • Ink Jet Receptive • Excellent Resistance to Scuff and Abrasion • Chemical Resistance • Heat Sealable for Flexible Packaging Applications • Hot Foil Stampable				
Web Width	40.1"				
Standard Length	5,000’ 10,000’ 20,000’				
Government Specs	21 CFR 177.1630, 21 CFR 175.105				

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.