

## Clear Advantage™ Selfwound Overlamination

<b>Product Description</b>	#U2000 Clear Polypropylene, Premium				
<b>Construction</b>	Film	Adhesive	Overall Thickness	Film Thickness	Adhesive Thickness
	Biaxially Oriented Polypropylene	Emulsion Acrylic	1.3 mil ± 5%	1.0 mil	0.3 mil
<b>Physical Properties</b>	Note: The following technical information and data should be considered representative or typical only.				
	Tensile Strength		16 lbs/in		
	Elongation at Break		120%		
	180° Peel Adhesion		12 oz/in		
<b>Special Features</b>	• Excellent resistance to chemical and abrasion				
<b>Temperature Range</b>	<b>Application Temperature</b>		<b>Operating Temperature</b>		
	41 ° F to 150 ° F		0 ° F to 200 ° F (nominal range)		
<b>Web Width</b>	63"				
<b>Standard Length</b>	5,000'/10,000'				
<b>Government Specs</b>	21 CFR 177.1520 & 21 CFR 175.105				

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.