

13226 Alondra Blvd., Cerritos, CA 90703 • www.achem-usa.com Tel: 562-802-0998 • 800-213-3321 Fax: 800-509-8273 • 562-802-5069

CS18H Hot Melt Tape

Product Description	 BOPP film coated tape General purpose packaging tape used for box sealing, splicing and other packaging applications. Hot melt pressure sensitive adhesive system with high adhesion, and holding power 	
Applications	 Multi-purpose packaging tape Suitable for lightweight carton sealing need Adheres instantly to variety of surfaces Edge tear and split resistance 	
Features/Benefits	 Economical and utility grade Biaxially Oriented Polypropylene (BOPP) tape Good Adhesion to fiberboard No known hazards 	
Construction	Film	Biaxially oriented polypropylene film
	Adhesive	Synthetic rubber
	Color	Clear
Physical Properties	Note: The following technical information and data should be considered representative or typical only.	
	Total Thickness	$0.045 \pm 0.002 \text{ mm } (1.8 \pm 0.08 \text{ mil})$
	Film Thickness	$0.028 \pm 0.001 \text{ mm } (1.1 \pm 0.04 \text{ mil})$
	Adhesion to steel	0.40 kg/cm (35.2 oz./in)
	Cohesion	10,000 minutes, 73° F (23° C)
	Tensile Strength	3.6 kg (19.8 lbs./in)
	Elongation at Break	100 ~ 180%
Storage	Recommended one-year shelf life from date of dispatch, if kept at moderate temperatures and humidity levels	

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.