

## CS20A Tape Rohm & Haas Tape

<b>Product Description</b>	<ul style="list-style-type: none"> <li>• Production grade pressure sensitive Carton Sealing Tape</li> <li>• Generally is used for box sealing applications</li> <li>• Construction provides a good closure for lightweight boxes exposed to minimal distribution hazards</li> </ul>	
<b>Construction</b>	Backing	Biaxially oriented polypropylene film
	Adhesive	Water-based acrylic Rohm & Haas
	Color	Clear
<b>Physical Properties</b>	Note: The following technical information and data should be considered representative or typical only. Total Thickness Allowance: $\pm 2$ microns	
	Total Thickness	0.050 mm (1.97 mil)
	Backing Thickness	0.028 mm (1.10 mil)
	Adhesion to steel	520g/in (18.3 oz/in)
	Holding Power	20 minutes
	Tensile Strength	10 kg/in (22.1 lb/in)
	Elongation at Break	175%
	Tack	20mm (0.83in)
<b>Available Sizes</b>	Standard Width	48 mm (2 in) & 72 mm (3 in)
	Core Size	72 mm (3 in)
	Length	50 M, 100 M, 914 M (55 yd, 110 yd, 1000 yd)
<b>Temperature Conditions</b>	Storage	Store in a clean, dry place. Temperature of 40°~80° F (4°~ 26° C) and 40%~ 50% relative humidity are recommended
	Application	-30°~200 ° F (-35°~93° C)
	Operating	32°~150° F (0°~65°C)

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.